

































$$\label{eq:product} \begin{array}{l} \hline \mbox{Dist} \m$$





































)			Swa	nsboro Me	thodist C Swanab W	hurch Si pro, NC Of hite Oak Riv	Anctuary (SLOW Col er Basin	and Mi	nistry Ce	nter					CDE
_				PROPOS	ED SP+ A 1	TRUCTUR	AL RUNOFI	VOLUM	E CONTROL	5					
Unter only runoff volume below that will be infiltrated or drawn down over 2 to 5 days. Additional volume provided in devices should not be entered in the worksheet. Drawdown time requirement applies to all storm events.															
Otha Ar	te Imponious ea Treated	2010	4]											
STORS	WATER CONT	ICL MEASURES									SIP & BHP Treatment Summary			*7	
scau				Contribut Inspervices pd)	Purvices (#)	S of Total Impervious	% of Total Pensional	Storage Volume	Dones. stream SCM	Drainogo Arma Inflow Volume	Tettal Infime Volume	billbation & ET	Ped Filtration Dathew	Treated Outflow	S of St Video
	larke / Location	Type of Device	MSG	125,848	222,438	Area	Area	64		618	618	34	54	14	UNKer
756	WE firms	Constructed Wetland	0	41.729	112,521	105	275	604		100	925	128	1	-793	1005
142 1-1	a DE Discorrected	Decementari Inservitus Type I	c	4.807		25	- 15		1	181	\$30	150		1	10.75
113 14	et 88 Pile 2955 De	Decomentati reperiosa 1 par 1	C	643		175	2%			73	73	33	8	- 4	100%
704	PreDe	Departmented Higher Have 3 year 2	c	10.985		77%	1%		781	1393	7,88	2185	8	8	500%
	Add Store	13000 of experiments are compared to 100848 of total matter Control Rose	esperious	compared to 3 compared to 3 goars Datase Bottors R	UNCE EXCLUSION	inpervisio and	period and								

















Project Profile

- Official Project name: A New Urban Outdoor Event Venue; Georgia Street Improvements
- Owner: City of Indianapolis, Indiana Department of Public Works
- Project Engineer: Crawford, Murphy & Tully, Inc., Indianapolis.
- Contractor: Hunt Construction Group, Indianapolis
- Architect: RATIO Architects, Inc., Indianapolis
- Precast Producer: Norwalk Concrete Industries, Norwalk, Ohio
- Precast Design Engineer: Delta Engineers, Architects, & Land Surveyors, PC, Endwell, New York



Project Scope

- Reconstruction of a three block stretch of Georgia Street leading to the entrance of Lucas Oil Stadium – site for the 2012 NFL Super Bowl
 - Inverted crown road cross-section to eliminate curbs and shed water to forebays
 - Includes a pedestrian promenade in the median strip consisting of a wooden boardwalk constructed on precast support beams
 - Cast-in-place underground sluiceway to collect rainwater and melted snow into cisterns for irrigation of the architectural landscaping

прся

Cast-in-place underground utility vaults









Precast Design Considerations

- · Member size and weight for shipping and handling
- Forming system
- Lifting devices, capacity and location
- · Joints and connections



Precast Design Concept





















Other Considerations











Specifying Precast

 Clear, concise specification is key to project success. Items to include in any specification:

- Applicable industry reference standards
- What should be expected with product submittal packages
- Appropriate design loads
- Concrete and material properties
- Producer qualifications

Specifying Precast

- Stock Items
- Many precasters stock various size items that are made to industry standards.
- Non-Stock Items
 - Custom utility structures can be made in unlimited sizes and shapes for a project.

Specifying Precast

Reference Standards and Submittals

- Applicable ASTM standard specifications – ASTM C857 – Min. Structural Design Loads for Precast Water and Watewater Structures
- ASTM C913 Standard Specification for Precast Water and Wastewater Structures
- ASTM C891 Practice for Installation of Precast Underground Utility Structures
- ASTM C990 Specification for Joints for Concrete Pipe, Manholes, and Precast Box Sections using Pre-formed Flexible Joint Sealants
- ASTM C1037 Practice for Inspection of Precast Underground Utility Structures

<section-header><section-header>

Specifying Precast

- ASTM C858 Standard Specification for Precast Concrete Water and Wastewater Structures
 - Contains a comprehensive list of ASTM standards for constituent materials and product testing. Included in the standard are:
 - Manufacturing Requirements
 - Design Standards
 - Permissible Variations
 - Repair Guidance
 - · Rejection of products which do not meet the standard
 - Product Marking

Super Bowl Pedestrian Promenade

??Questions??

Ronald E. Thornton, PE

rthornton2@stny.rr.com

	Programs						
1	Illicit Discharge Detection and Elimination Program						
2	Stormwater System Inventory and Prioritization Program						
3	BMP Retrofits						
4	BMP Toolbox for Post-Construction Runoff						
5	BMP Inspection and Maintenance Program						
6	Post-Construction Stormwater Program						
7	Vegetation Management						
8	Encroachment Program						
9	Construction Stormwater/Erosion Control						
10	Industrial Facilities						
11	Education and Involvement Program						
12	Research and Program Assessment						
13	Total Maximum Daily Loads						
14	Falls and Jordan Lake Nutrient Management Strategy Compliance						

Recent Updates
Illicit Discharge Detection and Elimination Program
Stormwater System Inventory and Prioritization Program
BMP Retrofits
BMP Toolbox for Post-Construction Runoff
BMP Inspection and Maintenance Program
Post-Construction Stormwater Program
Vegetation Management
Encroachment Program
Construction Stormwater/Erosion Control
Industrial Facilities
Education and Involvement Program
Research and Program Assessment
Total Maximum Daily Loads
Falls and Jordan Lake Nutrient Management Strategy Compliance

Post-Construction Stormwater Program Update

- Updated stormwater management policy for new DOT projects
- Consolidated State SW permitting under this program

Stormwater BMP Toolbox Objectives Maintain and update as necessary a BMP Toolbox to aid in the siting, design, and construction of stormwater quality BMPs with guidance on the suitability of each for NCDOT applications. Evaluate BMPs for applicability to the linear highway system. Implement new and innovative technology on an experimental basis and in keeping with the current DWQ policy on new stormwater treatment technologies.

Stormwater BMP Toolbox Toolbox Chapters

2014 New Chapters

Wet detention basin

· Stormwater wetland

Media filters

2008 Chapters

- Level spreader
- Preformed scour hole
- Dry detention basin
- Swale
- Forebay
- Hazardous spill basin
- Bridge Best Management Practices
- Infiltration basin

NPCA

- SMP tool is an excel based form for documenting compliance with the PCSP
- SMP tool has been revised to address 2014 Toolbox component.
- SMP training modules will be available once the 2014 Toolbox is launched.

прса

BMP Retrofits Objectives

- Develop, implement and support the NCDOT program to be consistent with NPDES post construction control measures.
- ii. Use retrofits to address pollutant loading from existing NCDOT activities.
- Retrofits should not be associated with meeting the requirements of any other DWQ program, unless otherwise allowed.

Research Objectives

- Conduct research with faculty and staff at state universities or other designated institutions that result in independent quantitative assessment of stormwater from NCDOT permitted activities and/or measure structural BMP effectiveness.
- b. Conduct research to enhance or improve existing practices or develop new methods or processes to meet future permit requirements.

