

RADIUS FEET	BOOM ANGLE	OVER REAR	OVER SIDE	OVER FRONT	BOOM ANGLE	OVER REAR	OVER SIDE	OVER FRONT	BOOM ANGLE	OVER REAR	OVER SIDE	OVER FRONT	
BOOM LENGTH 23 FT. BOOM					30 FT. BOOM					37 FT. BOOM			
8	72	40,000	40,000	40,000									
10	67	40,000	40,000	40,000	73	40,000	40,000	40,000					
12	61	40,000	40,000	40,000	69	40,000	40,000	40,000	74	39,100	39,100	39,100	
15	51	37,400	37,400	37,400	62	34,700	34,700	34,700	69	32,900	32,900	32,900	
18	39	30,100	32,500	32,500	55	30,100	30,300	30,300	64	28,600	28,600	28,600	
20	29	26,700	29,500	29,500	50	26,700	28,000	28,000	60	26,400	26,400	26,400	
25					34	19,800	18,700	23,400	50	21,000	18,900	22,300	
30									37	15,700	13,800	19,200	
35									18	12,200	10,800	15,200	
36									0	11,300	10,300	12,800	
		PART LINE	MAXIMUM LOAD										
		1	8,340										
		2	16,680										
		3	25,020										
		4	33,360										
		5	40,000										

MODEL NUMBER
5037R

RATED LIFTING CAPACITIES
OUTRIGGERS FULLY EXTENDED

SERIAL NUMBER
02141519025

1. DEDUCTION FROM RATED LIFTING CAPACITIES MUST BE MADE FOR THE WEIGHT OF LOAD BLOCK, SLINGS, OR ANY OTHER EQUIPMENT USED TO HANDLE OBJECTS BEING LIFTED.
2. LOADS MUST BE FREELY SUSPENDED, DO NOT EXCEED LOAD BLOCK OR PARTS OF LINE RATINGS.
3. BOOM ANGLES REFLECT CORRECTED ANGLE AFTER LOAD APPLIED.
4. LOADS ABOVE DASHED LINE ARE BASED ON STRUCTURAL LIMITS, BELOW LINE ON STABILITY.
5. READ AND UNDERSTAND OWNERS MANUAL BEFORE OPERATING.